



Car Subwoofer Driver
Die-casting Aluminium Basket
Glassfibre Cone With High Density Foam Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1001	SUW-MA1201	SUW-MA1501
Size	10"	12"	15"
Power (RMS)	1500W	2000W	2500W
Power (MAX)	3000W	4000W	5000W
Frequency Response	42Hz - 800Hz	38Hz - 800Hz	35Hz - 800Hz
Efficiency @1W/1M	90dB	90dB	90dB
Impedance	1 Ohm x 2	1 Ohm x 2	1 Ohm x 2
Voice Coil	3"	3"	3"
Magnet	200oz	200oz	250oz



Car Subwoofer Driver
Die-casting Aluminium Basket
Non-pressed Paper Cone With High Density Foam Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1002	SUW-MA1202	SUW-MA1502
Size	10"	12"	15"
Power (RMS)	1200W	1500W	2000W
Power (MAX)	2400W	3000W	4000W
Frequency Response	35Hz~1KHz	32Hz~1KHz	30Hz~1KHz
Efficiency @1W/1M	90dB	90dB	90dB
Impedance	2 Ohms x 2	2 Ohms x 2	2 Ohms x 2
Voice Coil	3"	3"	3"
Magnet	120oz	150oz	200oz



Car Subwoofer Driver
Stamped Steel Basket
Non-pressed Paper Cone With High Density Foam Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1003	SUW-MA1203
Size	10"	12"
Power (RMS)	1500W	2000W
Power (MAX)	3000W	4000W
Frequency Response	35Hz~1KHz	32Hz~1KHz
Efficiency @1W/1M	90dB	90dB
Impedance	4Ohms x 2	4Ohms x 2
Voice Coil	3"	3"
Magnet	200oz	200oz



Car Subwoofer Driver
Stamp Steel Basket
Non-pressed Paper Cone With High Quality Rubber Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1004	SUW-MA1204
Size	10"	12"
Power (RMS)	350W	450W
Power (MAX)	700W	900W
Frequency Response	32Hz~1KHz	30Hz~1KHz
Efficiency @1W/1M	90dB	90dB
Impedance	4 Ohms x 2	4 Ohms x 2

Voice Coil	2"	2"
Magnet	100oz	100oz



Car Subwoofer Driver
Stamp Steel Basket
Non-pressed Paper Cone With High Density Foam Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1005	SUW-MA1205
Size	10"	12"
Power (RMS)	300W	400W
Power (MAX)	600W	800W
Frequency Response	35Hz~1KHz	32Hz~1KHz
Efficiency @1W/1M	88dB	88dB
Impedance	4 Ohms	4 Ohms
Voice Coil	2"	2"
Magnet	80oz	80oz



Car Subwoofer Driver
Stamp Steel Basket
Polypropylene Cone With High Quality Rubber Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1006	SUW-MA1206
Size	10"	12"
Power (RMS)	250W	300W
Power (MAX)	500W	600W
Frequency Response	35Hz~1KHz	32Hz~1KHz
Efficiency @1W/1M	88dB	88dB
Impedance	4 Ohms	4 Ohms
Voice Coil	2"	2"
Magnet	50oz	50oz



Shallow Design Car Subwoofer Driver
Stamped Steel Basket
Paper Cone With High Density Foam Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1007S	SUW-1207S
Size	10"	12"
Power (RMS)	250W	300W
Power (MAX)	500W	600W
Frequency Response	48Hz~1KHz	45Hz~1KHz
Efficiency @1W/1M	90dB	90dB
Impedance	4 Ohms	4 Ohms
Voice Coil	2"	2"
Magnet	60oz	60oz



Shallow Design Car Subwoofer Driver
Stamped Steel Basket
Paper Cone With High Quality Rubber Surround
High Temperature 4 Layer Voice Coil
High Performance Ferrite Magnet Structure

Specifications	SUW-MA1008S	SUW-MA1208S
Size	10"	12"
Power (RMS)	200W	250W
Power (MAX)	400W	500W
Frequency Response	38Hz - 1KHz	35Hz~1KHz

Efficiency @1W/1M	88dB	88dB
Impedance	4 Ohms	4 Ohms
Voice Coil	2"	2"
Magnet	50oz	50oz



Car Subwoofer Driver
 Small Size But Produce High Power
 Die-casting Aluminium Basket
 Non-pressed Paper Cone With High Density Foam Surround
 High Temperature 4 Layer Voice Coil
 High Performance Ferrite Magnet Structure

Specifications	SUW-MA6509	SUW-MA8009
Size	6.5"	8"
Power (RMS)	300W	350W
Power (MAX)	600W	700W
Frequency Response	45Hz - 1KHz	42Hz - 1KHz
Efficiency @1W/1M	89dB	89dB
Impedance	2Ohms x 2	2Ohms x 2
Voice Coil	2"	2"
Magnet	80oz	200oz



Car Subwoofer Driver
 Small Size But Produce High Power
 Stamp Steel Basket
 Non-pressed Paper Cone With High Density Foam Surround
 High Temperature 4 Layer Voice Coil
 High Performance Ferrite Magnet Structure

Specifications	SUW-MA8010
Size	8"
Power (RMS)	300W
Power (MAX)	600W
Frequency Response	35Hz-1KHz
Efficiency @1W/1M	90dB
Impedance	2 Ohms x 2
Voice Coil	2"
Magnet	80oz



Active Powered Bass Tube System

Silent Effect Noise Elimination Circuit
High Efficiency MOSFET Amplifier
Variable Subwoofer Bass Boost Control
Heat Regulating Aluminium Heat Sink

Remote Control For Cabin Bass Control
Variable Low Pass Filter Crossover
Sensitivity Synchronization Control
High and Low Level Input Options

Specifications	SUB-MA08TA	SUB-MA10TA	SUB-MA12TA
Woofer Size	8"	10"	12"
Woofer Voice Coil	1.5"	2"	2"
Woofer Magnet	30oz	40oz	40oz
RMS Power	150W	160W	180W
Frequency Response	35Hz~250Hz	28Hz~250Hz	25Hz~250Hz
Signal-to-Noise Ratio	95dB	95dB	95dB



Active Powered Slim MDF Enclosure System Proper For Rear Mounting

Silent Effect Noise Elimination Circuit
High Efficiency DIGITAL Amplifier
Variable Subwoofer Bass Boost Control
Heat Regulating Aluminium Heat Sink
Switchable Speaker Phase Selection

Remote Control For Cabin Bass Control
Variable Low Pass Filter Crossover
Plastic Reinforced Impact Resistant Grilles
Sensitivity Synchronization Control
High and Low Level Input Options

Specifications	SUB-MA10SRA	SUB-MA12SRA
Woofer Size	10"	12"
Woofer Voice Coil	2"	2"
Woofer Magnet	40oz	40oz
RMS Power	160W	180W
Frequency Response	28Hz~250Hz	25Hz~250Hz
Signal-to-Noise Ratio	95dB	95dB
Phase Switch	0-180	0-180



Active Powered Extra Slim MDF Enclosure System

Silent Effect Noise Elimination Circuit
High Efficiency DIGITAL Amplifier
Variable Subwoofer Bass Boost Control
Heat Regulating Aluminium Heat Sink
Switchable Speaker Phase Selection

Remote Control For Cabin Bass Control
Variable Low Pass Filter Crossover
Plastic Reinforced Impact Resistant Grilles
Sensitivity Synchronization Control
High and Low Level Input Options

Specifications	SUB-MA10SSA	SUB-MA12SSA
Woofer Size	10"	12"
Woofer Voice Coil	2"	2"
Woofer Magnet	40oz	40oz
RMS Power	160W	180W
Frequency Response	28Hz~250Hz	25Hz~250Hz
Signal-to-Noise Ratio	95dB	95dB
Phase Switch	0-180	0-180



Active Powered Vented Bass Enclosure System

Silent Effect Noise Elimination Circuit
High Efficiency MOSFET Amplifier
Variable Subwoofer Bass Boost Control
Heat Regulating Aluminium Heat Sink

Remote Control For Cabin Bass Control
Variable Low Pass Filter Crossover
Sensitivity Synchronization Control
High and Low Level Input Options

Specifications	SUB-MA10SPA	SUB-MA12SPA
Woofer Size	10"	12"
Woofer Voice Coil	2"	2"
Woofer Magnet	40oz	40oz
RMS Power	160W	180W
Frequency Response	28Hz~250Hz	25Hz~250Hz
Signal-to-Noise Ratio	95dB	95dB



Passive Powered Vented Bass Enclosure

High Quality MDF Construction
Carpet Covered
Plastic Reinforced Impact Resistant Grilles
Dual Woofers Loaded

Specifications	SUB-MA10DP	SUB-MA12DP
Woofer Size	10" x 2	12" x 2
Woofer Voice Coil	2"	2"
Woofer Magnet	40oz	40oz
RMS Power	400W	500W
MAX Power	800W	1000W
Frequency Response	35Hz~1KHz	32Hz~1KHz



Professional Midrange Speaker

Steel Basket

Non-pressed Paper Cone With Cloth Surround

Bulid With Aluminium Phase Plug

Model	PRO-MA6501	PRO-MA8001
Size	6.5"	8"
Power (RMS)	250Watts	300Watts
Power (MAX)	500Watts	600Watts
Frequency Response	100Hz~10KHz	80Hz~10KHz
Efficiency @1W/1M	97dB	98dB
Impedance	4 Ohm / 8 Ohm	4 Ohm / 8 Ohm
Voice Coil	1.5"	1.5"
Magnet	90x6 NdFeB	90x6 NdFeB



Professional Midrange Speaker

Aluminium Basket

Non-pressed Paper Cone With Cloth Surround

Bulid With Aluminium Phase Plug

Model	PRO-MA6502	PRO-MA8002
Size	6.5"	8"
Power (RMS)	250Watts	300Watts
Power (MAX)	500Watts	600Watts
Frequency Response	130Hz~10KHz	100Hz~10KHz
Efficiency @1W/1M	95dB	95dB
Impedance	4 Ohm / 8 Ohm	4 Ohm / 8 Ohm
Voice Coil	1.5"	1.5"
Magnet	35oz	50oz



Professional Midrange Speaker

Steel Basket

Non-pressed Paper Cone With Cloth Surround

Bulid With Aluminium Phase Plug

Model	PRO-MA6503	PRO-MA8003
Size	6.5"	8"
Power (RMS)	250Watts	300Watts
Power (MAX)	500Watts	600Watts
Frequency Response	100Hz~10KHz	80Hz~10KHz
Efficiency @1W/1M	95dB	95dB
Impedance	4 Ohm / 8 Ohm	4 Ohm / 8 Ohm
Voice Coil	1.5"	1.5"
Magnet	35oz	50oz



Professional Square Midrange Speaker

Steel Basket

Paper Cone With Cloth Surround

Bulid With Aluminium Phase Plug

Model	PRO-MA6004
Size	8"
Power (RMS)	250Watts
Power (MAX)	500Watts
Frequency Response	85Hz~15KHz
Efficiency @1W/1M	92dB
Impedance	4 Ohm / 8 Ohm
Voice Coil	1.5"
Magnet	35oz



Professional Midrange Speaker
Sealed Steel Basket
Non-pressed Paper Cone With Cloth Surround
Bulid With Aluminium Phase Plug

Model	PRO-MA6505	PRO-MA8005
Size	6.5"	8"
Power (RMS)	250Watts	300Watts
Power (MAX)	500Watts	600Watts
Frequency Response	600Hz~12KHz	500Hz~12KHz
Efficiency @1W/1M	95dB	95dB
Impedance	4 Ohm / 8 Ohm	4 Ohm / 8 Ohm
Voice Coil	1.5"	1.5"
Magnet	35oz	50oz



Professional Shallow Design Midrange Speaker
Steel Basket
Paper Cone With Cloth Surround
Bulid With Aluminium Phase Plug

Model	PRO-MA6506	PRO-MA8006
Size	6.5"	8"
Power (RMS)	150Watts	200Watts
Power (MAX)	300Watts	400Watts
Frequency Response	150Hz~10KHz	120Hz~10KHz
Efficiency @1W/1M	95dB	95dB
Impedance	4 Ohm / 8 Ohm	4 Ohm / 8 Ohm
Voice Coil	1.5"	1.5"
Magnet	20oz	30oz



Professional Midrange Speaker
Steel Basket
Paper Cone With Cloth Surround
Bulid With Aluminium Phase Plug

Model	PRO-MA65607	PRO-MA8007
Size	6.5"	8"
Power (RMS)	150Watts	200Watts
Power (MAX)	300Watts	400Watts
Frequency Response	120Hz~10KHz	90Hz~10KHz
Efficiency @1W/1M	95dB	95dB
Impedance	4 Ohm / 8 Ohm	4 Ohm / 8 Ohm
Voice Coil	1.5"	1.5"
Magnet	20oz	30oz



Coaxial Speaker System

Woofer: Steel Basekt, Polypropylene Cone With Butyl Surround

Tweeter: Built With Mylar Dome Diaphragm



Specifications	COA-MA4031	COA-MA5031	COA-MA6531	COA-MA6931
Size	4" 3-Way	5.25" 3-Way	6.5" 4-Way	6x9" 4-Way
Woofer Magnet	6oz	8oz	10oz	21.6oz
Woofer Voice Coil	1"	1"	1"	1"
Power (RMS)	80W	100W	120W	200W
Power (MAX)	160W	200W	240W	400W
System Frequency Response	110Hz~20KHz	90Hz~20KHz	80Hz~20KHz	50Hz~20KHz
System Efficiency @1W/1M	90dB	90dB	90dB	90dB
System Impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms



Coaxial Speaker System

Woofer: Steel Basekt, Polypropylene Cone With Butyl Surround

Tweeter: Built With Mylar Dome Diaphragm



Specifications	COA-MA4032	COA-MA5032	COA-MA6532	COA-MA6942
Size	4" 3-Way	5.25" 3-Way	6.5" 4-Way	6x9" 4-Way
Woofer Magnet	3.5oz	3.5oz	3.5oz	11.5oz
Woofer Voice Coil	0.75"	0.75"	0.75"	1"
Power (RMS)	40W	50W	60W	80W
Power (MAX)	80W	100W	120W	160W
System Frequency Response	120Hz~18KHz	100Hz~15KHz	80Hz~18KHz	50Hz~18KHz
System Efficiency @1W/1M	88dB	88dB	88dB	90dB
System Impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms



2 Way Component System

Woofer: Steel Basket

Aluminium Cone With Butyl Rubber Surround

Dome Glassfibre Dustcap

1.5" High Temperature Power Voice Coil

20oz Ferrite Magnet Structure

Tweeter: Build With Titanium Dome Diaphragm, 1 Inch Voice Coil

Include Flush and Surface Mounts

Crossover: 12dB/oct

Specifications	COM-MA0501	COM-MA0601
Woofer Size	5.25"	6.5"
Power (RMS)	90W	100W
Power (MAX)	180W	200W
System Frequency Response	100Hz~20KHz	90Hz~20KHz
System Efficiency @1W/1M	90dB	90dB
System Impedance	4 Ohms	4 Ohms



2 Way Component System

Woofer: Steel Basket

Polypropylene Cone With Butyl Rubber Surround

Aluminium Bullet

1" High Temperature Power Voice Coil

15oz Ferrite Magnet Structure

Tweeter: Build With Silk Dome Diaphragm, 1 Inch Voice Coil

Include Flush and Surface Mounts

Crossover: 12dB/oct

Specifications	COM-MA0502	COM-MA0602
Woofer Size	5.25"	6.5"
Power (RMS)	80W	90W
Power (MAX)	160W	180W
System Frequency Response	110Hz~20KHz	100Hz~20KHz
System Efficiency @1W/1M	90dB	90dB
System Impedance	4 Ohms	4 Ohms